

# iConnex

## Data Sheet ENG-155-0000



**E11** 10R05/01 11558

|  |  |
|--|--|
| Module Supply Voltage Range                      | 9-32V  |
| Digital Inputs                                   | 6  |
| Analog Inputs                                    | 2  |
| Outputs  | 10x FET & 2x Dry Contact Relay (NO/NC)                               |
| Positive FET Output Current Max (Self Protected) | 8A   |
| Negative FET Output Current Max (Self Protected) | 1A   |
| Relay Contacts Current Max                       | 30A  |
| Supply Fuse Rating Max (10mm Cable)              | 70A  |
| Input Voltage Range                              | 0-32V  |
| CAN-Bus Baud Rates                               | 50 Kbps<br>83.3 Kbps<br>100 Kbps<br>125 Kbps<br>250 Kbps<br>500 Kbps |
| Standby Current Consumption                      | 29mA   |
| Sleep Mode Current Consumption                   | 19mA   |
| Connector Type                                   | Molex Mini-Fit Jr. Series  |
| Weight   | 367g   |
| Dimensions L x W x H                             | 135 x 165 x 49 (mm)  |
| Module Expansion                                 | Up to 5 Modules Total (4 Slaves)                                     |
| Keypad Expansion                                 | Up to 5 Keypads Total  |

# iConnex

## Drill Hole Template ENG-155-0000

