

320 Channel PMC CPU, Central Processing Unit

Date datasheet created:
16/05/2013

The PMC CPU, part number 00-01015-120/-240, is the main component of Intellitec's Programmable Multiplex Control family. This is the next generation for the PMC family and replaces the following part number, 00-00800-022/-240. For additional information, please refer to the following technical brief, document Tehnical Application Brief _july_08.

The PMC CPU controls remote I/O modules through Intellitec's multiplex communications system (Pat. No. 4,907,222 and 6,011,997). This multiplex system allows the CPU, I/O Modules and switch panels to be wired together with two wires.

This CPU is identical to its' predecessor having two identical, 4-pin, Amp Mate-N-Lok connectors. Pin 1 provides a fused 12 volt power source to power things like switch back lighting. Pins 2 and 3 are the multiplex signals (two loops of 160 channels each) which communicate instructions to and from each of the I/O modules, Pin 4 is multiplex communication ground.

All the harnesses are connected with AMP, Mate-N-Lok connectors to reduce installation time and errors. Combine the Programmable Multiplex Control Central Processing Unit with the Intellitec standard, semi-custom or custom modules, and you can create the exact system configuration that you want, from basic to all encompassing.


What is a PMC System

A system can be as small as one CPU and one I/O module, or it can communicate with up to 32 I/O modules. Each module can have a combination of up to 10 inputs, or outputs.

Multiple modules can be wired to a single connector. All input, or switch information is gathered through the remote modules and directly communicated to the CPU. The CPU then interprets the inputs, determines the states of all outputs and communicates that information to the remote modules via the PMC communications link (pins 2 and 3).

How Does the CPU Communicate to Modules

The PMC system communicates continually at a relatively slow rate of 4 kHz. Each input/output is updated every .040 seconds. The multiplex signal, communicates to the output modules with a large change in signal voltage.



This slow communications rate and large signal voltage change makes the PMC system extremely resistant to interference from EMI and RFI. Because of the low communications frequency and large signal change, communication can take place without fear of interference over any economical wire and eliminates the need for special cables and connectors.

The approximate module dimensions are 6.375" X 6.250" X 1.875" (16.2mm X 15.9mm X 4.8mm). The module should be installed in a protected environment inside of the vehicle.

PMC CPU Features

The CPU has the following features:

- + 32 modules fully programable and addressable
- + Total of 320 channels of configurable inputs and outputs
- + 160 channels of Programmable Timers (These timers can function as on/delay, off/delay, flasher and interval timers, eliminating the need for special flasher modules, mirror heat timers, wiper delays, load managers, etc.)
- + 160 Virtual Channels available for more complex application development (Provides the capability to write very complex logic relationships between the channels.)

+Sleep Mode operation with improved low power consumption (Allowing for the system to be constantly live with insignificant drain on the vehicle battery.)

+Reduction in time for transferring and retrieving PMC application files (The application program resides in Flash memory and is retained when power is removed from the CPU.)

320 Channel PMC CPU, Central

Date datasheet created:
16/05/2013


Processing Unit

The CPU RS-232C communications port and Windows software is used to setup or program the vehicle specific requirements. The port can also be used to perform system diagnostics. If a lap top isn't available most diagnostics can be performed with a volt meter.

Through the use of Intellitec's WinPMC II Windows based software program and the connection of a PC to the RS-232C port, the user can easily set up the relationships between the switch inputs, timers and outputs.

Specifications

| | | |
|---------------|-----------------|-----------------------|
| Part Number | 00-01015-120 | 00-01015-240 |
| Voltage | 12V | 24V |
| Voltage Range | up to +16 Volts | +10 Volts to 36 Volts |



CONNECTOR PIN DESIGNATIONS

| | | |
|-------|-------------------------------------|--|
| J4 | RS-232C | PC Communications (Note 1) |
| J2-J3 | PMC Communications | (All three connectors identical) |
| Pin 1 | Fused Power for remote backlighting | 16 awg Min. Fuse F2 5 Amps Max. |
| Pin 2 | Multiplex Signal Blue Loop | 16 awg Min. (see Chapter 3 of the Users Guide) |
| Pin 3 | Multiplex Signal Yellow Loop | 16 awg Min. (see Chapter 3 of the Users Guide) |
| Pin 4 | Communications Ground | 14 awg Min. (Make no other connections) |
| J1-1 | Battery | Fuse F1 10 Amps Max. |
| J1-2 | Ground | |
| J1-3 | Aux In 1 (+12V disables sleep mode) | Sleep Mode 4.7K Input Impedance |
| J1-4 | Aux In 2 (+12V disables sleep mode) | Sleep Mode 4.7K Input Impedance |

MATING CONNECTIONS

| Designator | Function | Connector | Mating Part # | Contact, Typical |
|------------|-----------|----------------------|---------------|------------------------|
| J1 | CPU Power | 5 Pin Amp Mate-N-Lok | 1-480763-0 | 350919-3 for 14-18 AWG |
| J2 | PMC Com | 4 Pin Amp Mate-N-Lok | 1-480702-0 | 350919-3 for 14-18 AWG |
| J3 | PMC Com | 4 Pin Amp Mate-N-Lok | 1-480702-0 | 350919-3 for 14-18 AWG |
| J4 | RS-232C | | RJ11 | (Note 1) |

| SYSTEM CAPACITY | |
|-------------------|-------------------|
| Program Memory | EPROM |
| User Memory | Non Volatile |
| Module Capacity | 32 |
| I/O per Module | 10 |
| Total I/O Control | 320 |
| Virtual Channels | 160 |
| Timer Channels | 160 |
| COMMUNICATIONS | |
| CPU/Module | PMC two wire 4KHZ |
| EMI/RFI | High Immunity |
| User PC Program | WinPMCI |

For further information on this product, please contact Intellitec.



www.intellitecmv.com